eurocol

500 EUROSAFE MULTI

Multi-purpose floor covering adhesive with a high initial grab.

Product Typification

Basis	:	Superior acrylic dispersion.
Colour	:	Beige.
Consistency	:	Thick liquid.

- Multi-purpose application
- Non-flammable
- Easy and safe to apply
- High initial adhesion strength and final bond strength
- Favourable spreading capacity
- Roller-castor-chair resistant

Performances

Specific weight	:	1.56 kg/l.
Flammability	:	Non-flammable.
Consumption	:	Spreader B1: 325 - 425 g/m². Spreader A2: 300 - 350 g/m².

Application

For installing:

- PVC and cushion vinyl flooring
- synthetic backed carpet
- hessian-backed carpet
- PVC backed-carpet
- needlefelt
- linoleum
- corkment

Working Process

Storage	:	Store cool and free from frost.
Tools	:	Eurocol spreader no. 850/B1 when installing carpet, needlefelt, linoleum and corkment. Eurocol spreader no. 852/A2 when installing carpet with a PVC back and PVC and cushion vinyl flooring.
Open time	:	15-30 minuten.*
Latency	:	0 - 10 minutes.*
Drying time	:	24 hours.*
Shelf Life	:	Approx 12 months, in unopened packaging.

* The mentioned values have been established in our laboratory and must be considered as guidelines in view of possible variations in climatic circumstances, subfloor compositions and layer thickness.

Substrate:

- 500 Eurosafe Multi is suitable for any type of subfloor that has a good tensile and compression strength. The subfloor should also be even, clean, permanently dry and free from grease and dirt, according to the requirements of BS 8203 or DIN 18 365.
- Only use vapour pervious floor coverings on impervious subfloors.
- When installing cushion vinyls or a carpet with a closed back on fully impervious subfloors apply a 2 mm levelling compound layer.
- In advance always seek our technical data sheets. In doubt about the application ask for technical advice.

User manual:

Working conditions:

Required surrounding temperature : 18° - 23° C.
Temperature for material and subfloor : min. 15° - max. 20º C.
Relative humidity : 40 - 80%.

Directions for use:

- Apply the adhesive with the recommended adhesive spreader.
  - Eurocol spreader no. 850/B1 for installing carpet, needlefelt, linoleum and corkment.
  - Eurocol spreader no. 852/A2 for installing PVC and cushion vinyl flooring and carpet with a PVC back.
- On absorbent subfloors apply the floor covering within 10 minutes into the wet adhesive. On low absorbent subfloors keep a waiting time of 10 - 30 minutes (depending on porosity of the subfloor, temperature and relative humidity).
- When installing PVC and cushion vinyl flooring and carpet with a PVC back the subfloor should be moisture absorbent and apply the floor covering into the wet adhesive.
- Roll the floor covering carefully. Sheet-ends, possible bight marks and longitudinal joints are to be pressed firmly.
- On low absorbent subfloors, in case of impervious back qualities and/or when circumstances are less ideal, rolling and pressing should be repeated after approx. 15 minutes (depending on temperature and relative humidity).
- Remove fresh adhesive spots immediately with water.

Underfloor heating systems:

500 Eurosafe Multi can be applied on underfloor heating systems. The startprotocol of the floorheating needs to be completly executed in accordance with the directives of the supplier. Turn off the heater 24 hours before application. Do not heat again until at least 24 hours after installation, in steps of maimun 5° C water temperature per day.

Quality and guarantee

Environment and health

Hazard Class	:	None.
Safety and environment	:	Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155.
MSDS	:	Available on request.

Articles

Article	Definition	Packaging	EAN-code
500	Eurosafe Multi	15 kg bucket	8 710345 515009

the strong connection